



Badger Meter

GALAXY®
Trimble® Ranger 3

OVERVIEW

The Trimble® Ranger 3 is a full-featured, handheld data collection computer. It combines a Windows® mobile operating system, ergonomic keypad and military-grade durability, providing a full day of continuous meter reading.

OPERATION

System: The Trimble Ranger 3 handheld uses a Windows mobile 6.5 Professional operating system.

Display: A large 4.2 inch, high resolution color, resistive touch screen with LED backlight supports reading in both sunlight and darkness.

Control: The Trimble Ranger 3 handheld features ergonomic navigation with versatile alpha and numeric keypads that are easy to use, even when wearing gloves. The user may also operate the handheld using the easy-to-navigate touch screen controls.

Power: A lithium ion rechargeable battery pack powers the Trimble Ranger 3 handheld, providing a full day of continuous usage under normal operating conditions.

The handheld may be charged using either the Office Docking Station or AC power supply that comes with the handheld. An optional DC power vehicle charger and spare battery are also available.

Performance: The Trimble Ranger 3 handheld was designed to meet MIL-STD-810G military standards for drops, vibration, humidity, altitude and extreme temperatures. With an IP67 rating, it is impervious to water, dust and the harsh conditions involved with utility usage.

GALAXY: A GALAXY equipped handheld can be used for programming endpoints and as a troubleshooting tool in the field.



STANDARD FEATURES

- Microsoft® Windows Mobile 6.5 Professional
- Custom keypad: 53 tactile keys with separate navigation, alpha and numeric keypads, and 8+1 directional pad
- Touch screen
- Full-day battery life under normal operating conditions
- Complete recharge in 4.0 hours (80% in 2 hours)
- Three tri-color notification LEDs
- Rugged polycarbonate case with Hytrel® overmold
- Integrated components:
 - Bluetooth® 2.0 + EDR
 - WiFi 802.11b/g
 - Speaker and microphone with 3.5 mm stereo headset/microphone port
 - GPS receiver
 - Electronic compass

STANDARD SOFTWARE

Badger Suite of Field Application Software

Admin and Kiosk Modes

Programming/Field Troubleshooting Software

Windows Mobile 6.5 Professional Operating System including the following:

Microsoft® Office Mobile

- Word® Mobile
- Excel® Mobile
- PowerPoint® Mobile
- Outlook® Mobile

Internet Explorer Mobile

- Contacts
- Tasks/Notes
- Calendar
- Calculator
- Adobe Acrobat® Reader
- Windows Media Player
- Microsoft Pictures and Videos
- Microsoft ActiveSync
- Online Help
- Trimble SatViewer (GPS interface application)

STANDARD ACCESSORIES

- Office docking station with power cord
- Rechargeable lithium-ion battery pack
- International AC power supply charging kit with four plug adapters
- Audio port dust cover
- I/O port dust cover
- Screen protectors (15-pack)
- Hand strap
- Touch screen stylus (2) with tether
- USB cable (mini)
- USB flash drive
- IR programming cable

PHYSICAL (without antenna)

Size 10.5" (26.6 cm) x 5.2" (13.1 cm) x 1.9" (4.8 cm)

Weight..... 2.3 lb (1.04 kg), including battery and stylus

ELECTRICAL

Processor..... Texas Instruments AM3715 Sitara® ARM® Cortex-A8 processor

Display.....4.2" landscape VGA 640 x 480 pixels sunlight readable TFT with LED backlight

Power..... Lithium-Ion rechargeable pack 2500 mAh (11.1 V)

I/O..... USB 2.0 full speed host and 2.0 high speed client; 15 V DC power port; 3.5 mm stereo and microphone audio port stereo; 9-pin RS-232 serial port

GPS Accuracy.....2-4 m with SBAS correction

ENVIRONMENT

Operating Temperature..... -22...140° F (-30...60° C)

Storage Temperature..... -40...158° F (-40...70° C)

Humidity..... MIL-STD-810G, Method 507.5

Water..... IP67, sealed against accidental immersion (1 m for 30 min.) IEC-529

Drop..... MIL-STD-810G, Method 516.6 Procedure IV 48" onto plywood over concrete 26 drops at room temperature (all faces, edges, corners, one drop each) 6 drops at 60° C, 6 drops at -30° C

Sand & Dust..... IP67, IEC-529

Vibration..... MIL-STD-810G, Method 514.6 Procedures I and II

Altitude..... MIL-STD-810G, Method 500.5 Procedures I, II, III, 15,000 ft at 73° F (23° C)

SPECIFICATIONS

Processor Speed.....Intel XScale, 800 MHz

Memory.....SDRAM ~256 MB
Data storage (on-board flash) ~8 GB
Secure digital (SD/SDHC) card slot

Wireless.....Integrated Bluetooth 2.0 + EDR and WiFi 802.11b/g, standard

Certifications.....FCC, IC (Canada), RoHS compliant
WiFi Alliance certified
MIL-STD-810G, IP67, MIL-STD 461

Making Water Visible®

GALAXY and Making Water Visible are registered trademarks of Badger Meter, Inc. Other trademarks appearing in this document are the property of their respective entities.

Due to continuous research, product improvements and enhancements, Badger Meter reserves the right to change product or system specifications without notice, except to the extent an outstanding contractual obligation exists. © 2014 Badger Meter, Inc. All rights reserved.

www.badgermeter.com

The Americas | Badger Meter | 4545 West Brown Deer Rd | PO Box 245036 | Milwaukee, WI 53224-9536 | 800-876-3837 | 414-355-0400

México | Badger Meter de las Americas, S.A. de C.V. | Pedro Luis Ogazón N°32 | Esq. Angelina N°24 | Colonia Guadalupe Inn | CP 01050 | México, DF | México | +52-55-5662-0882

Europe, Middle East and Africa | Badger Meter Europa GmbH | Nurtlinger Str 76 | 72639 Neuffen | Germany | +49-7025-9208-0

Europe, Middle East Branch Office | Badger Meter Europe | PO Box 341442 | Dubai Silicon Oasis, Head Quarter Building, Wing C, Office #C209 | Dubai / UAE | +971-4-371 2503

Czech Republic | Badger Meter Czech Republic s.r.o. | Mařikova 2082/26 | 621 00 Brno, Czech Republic | +420-5-41420411

Slovakia | Badger Meter Slovakia s.r.o. | Raciánska 109/B | 831 02 Bratislava, Slovakia | +421-2-44 63 83 01

Asia Pacific | Badger Meter | 80 Marine Parade Rd | 21-06 Parkway Parade | Singapore 449269 | +65-63464836

China | Badger Meter | 7-1202 | 99 Hangzhong Road | Minhang District | Shanghai | China 201101 | +86-21-5763 5412